

# Shaft Supports L-Shaped (Machined)

Standard / Slit, H-Selectable/Configurable

**Standard**

**RoHS**

Height H Selectable Type	Height H Configurable Type	Material	Surface Treatment	Accessories
SHKLB	SHKLBH	1045 Carbon Steel	Black Oxide	Hex Socket Head Cap Screw 1 pc. Set Screw 1 pc.
SHKLM	SHKLMH	304 Stainless Steel	Electroless Nickel Plating	Hex Socket Head Cap Screw 1 pc. Set Screw 1 pc. (Stainless Steel)
SHKLS	SHKLSH		-	
SHKLA	-	6063 Aluminum Alloy	Clear Anodize	-

Part Number	H												Unit Price											
	Type	D	Height Selectable Type				L	H1	T	S	W	W1	Set Screw M	L1	d	Height Selectable Type			Height Configurable Type					
			SHKLB	SHKLM	SHKLS	SHKLA										SHKLBH	SHKLMH	SHKLSH						
Height H Selectable Type	3	10	15	20																				
	4	10	15	20	10.0-20.0																			
	5	15	20	25	15.0-25.0																			
	6	15	20	25	15.0-40.0																			
	8	15	20	25	30	40	20.0-40.0																	
	10	20	25	30	40																			
Height H Configurable Type	12	20	25	30	40																			
	13	20	25	30	40																			
	16	20	25	30	40	20.0-40.0																		
	20	25	30	40	50	60	25.0-60.0																	
	25	30	40	50	60	30.0-60.0																		
	30	35	40	50	60	35.0-60.0																		
	35	40	50	60	40.0-60.0																			
	40	40	50	60	80	40.0-80.0																		
	50	50	60	80	50.0-80.0																			

**Slit**

**RoHS**

\*D3, D4 and D5 have 4 mm deeper slits.

Slit is machined after the mounting hole D is bored to H<sub>z</sub> tolerance. Tolerance may become H<sub>s</sub> depending on the machining condition.

Height H Selectable Type	Height H Configurable Type	Material	Surface Treatment	Accessories
SHKSB	SHKSBH	1045 Carbon Steel	Black Oxide	Hex Socket Head Cap Screw 1 pc.
SHKSM	SHKSMH	304 Stainless Steel	Electroless Nickel Plating	Hex Socket Head Cap Screw 1 pc. (Stainless Steel)
SHKSS	SHKSSH		-	
SHKSA	SHKSAH	6063 Aluminum Alloy	Clear Anodize	-
SHKSD	-	Aluminum Alloy	Black Anodize	Hex Socket Head Cap Screw 1 pc.

Part Number	H												Unit Price													
	Type	D	Height Selectable Type				L	H1	T	S	W	W1	L1	d	E	Tightening Screw M	d2	d1	ℓ	C	Height Selectable Type			Height Configurable Type		
			SHKSB	SHKSM	SHKSS	SHKSA															SHKSD	SHKSBH	SHKSMH	SHKSAH		
Height H Selectable Type	3	10	15	20																						
	4	10	15	20	10.0-20.0																					
	5	15	20	25	15.0-25.0																					
	6	15	20	25	15.0-25.0																					
	8	15	20	25	30	40	15.0-40.0																			
	10	20	25	30	40	20.0-40.0																				
Height H Configurable Type	12	20	25	30	40																					
	13	20	25	30	40																					
	16	20	25	30	40	20.0-40.0																				
	20	25	30	40	50	60	25.0-60.0																			
	25	30	40	50	60	30.0-60.0																				
	30	35	40	50	60	35.0-60.0																				
	35	40	50	60	40.0-60.0																					
	40	40	50	60	80	40.0-80.0																				
	50	50	60	80	50.0-80.0																					

Ordering Example: Part Number - H  
 SHKLM8 - 25  
 SHKLMH8 - 25.6

Days to Ship: Configure Online

Price: Configure Online

# Shaft Supports L-Shaped (Machined)

Side Slit / Split, H-Selectable/Configurable

**Side Slit**

**RoHS**

Slit is machined after the mounting hole D is bored to H<sub>z</sub> tolerance. Tolerance may become H<sub>s</sub> depending on the machining condition.

Pilot hole for tapped hole M may be through.

Height H Selectable Type	Height H Configurable Type	Material	Surface Treatment	Accessories
SHKWB	SHKWMH	1045 Carbon Steel Equivalent	Black Oxide	Hex Socket Head Cap Screw 1 pc.
SHKWS	SHKWSH	304 Stainless Steel	Electroless Nickel Plating	Hex Socket Head Cap Screw 1 pc. (Stainless Steel)
SHKWA	SHKWAH	6063 Aluminum Alloy	Clear Anodize	Hex Socket Head Cap Screw 1 pc.
SHKWD	SHKWDH		Black Anodize	

Part Number	H												Unit Price													
	Type	D	Height Selectable Type				L	H1	T	S	W	W1	L1	d	E	Tightening Screw M	d2	d1	ℓ	C	Height Selectable Type			Height Configurable Type		
			SHKWB	SHKWM	SHKWS	SHKWA															SHKWD	SHKWMH				
Height H Selectable Type	8	15	20	25	30	40	15.0-40.0																			
	10	20	25	30	20.0-30.0																					
	12	20	25	30	20.0-30.0																					
	13	20	25	30	20.0-30.0																					
	16	20	25	30	40	20.0-40.0																				
	20	25	30	40	50	60	25.0-60.0																			
Height H Configurable Type	25	30	40	50	60	30.0-60.0																				
	30	30	40	50	60	30.0-60.0																				
	35	40	50	60	40.0-60.0																					
	40	40	50	60	80	40.0-80.0																				

**Split**

**RoHS**

Pilot hole for tapped hole M may be through.

Height H Selectable Type	Height H Configurable Type	Material	Surface Treatment	Accessories
SHKPB	SHKPMH	1045 Carbon Steel	Black Oxide	Hex Socket Head Cap Screw 2 pcs.
SHKPM	SHKPSH	304 Stainless Steel	Electroless Nickel Plating	Hex Socket Head Cap Screw 2 pcs. (Stainless Steel)
SHKPA	SHKPAH	6063 Aluminum Alloy	Clear Anodize	Hex Socket Head Cap Screw 2 pcs.
SHKPD	SHKPDH		Black Anodize	

Part Number	H												Unit Price													
	Type	D	Height Selectable Type				L	H1	T	S	W	W1	L1	d	E	Tightening Screw M	d2	d1	ℓ	C	Height Selectable Type			Height Configurable Type		
			SHKPB	SHKPM	SHKPS	SHKPA															SHKPD	SHKPMH	SHKPSH	SHKPAH		
Height H Selectable Type	3	10	15	20	10.0-20.0																					
	4	10	15	20	10.0-20.0																					
	5	15	20	25	15.0-25.0																					
	6	15	20	25	15.0-25.0																					
	8	15	20	25	30	40	15.0-40.0																			
	10	20	25	30	20.0-30.0																					
Height H Configurable Type	12	20	25	30	20.0-30.0																					
	13	20	25	30	20.0-30.0																					
	16	20	25	30	40	20.0-40.0																				
	20	25	30	40	50	60	25.0-60.0																			
	25	30	40	50	60	30.0-60.0																				
	30	30	40	50	60	30.0-60.0																				
	35	40	50	60	40.0-60.0																					
	40	40	50	60	80	40.0-80.0																				
	50	50	60	80	50.0-80.0																					

Ordering Example: Part Number - H  
 SHKWS20 - 30  
 SHKPSH20 - 30.6

Days to Ship: Configure Online

Price: Configure Online

Example: Combination of these use examples can be selected over Web. Details about Selection Procedure. P81

e-Catalog Search Key #MA822 Search

"If a search key is inputted in e-Catalog Search BOX, the search result is shown on the right side of the screen, "Module Assembler" area.