


8. 13. 14 O-RING SPEC.

MATERIAL	NBR
	FPM
	SILICON

9. SEAT MATERIAL

MATERIAL	SCS 13
	SCS 14

24	NUT	S 45C	6	
23	SPRING SEAT (UPP)	SNB 7	6	
22	ADJUST SPRING(UP)	SWOSC	1	
21	ADJUST SPRING(OUT)	SWOSC	1	
20	SPRING	SUS 304	1	
19	PLUG GASKET	PTFE	1	
18	LOCK NUT	C 3604	1	
17	ADJUST SCREW	C 3604	1	
16	SPRING SEAT(UPP.)	SS 400	1	
15	SPRING SEAT(LOW.)	SS 400	1	
14	O-RING	SEE TABLE	1	
13	O-RING	SEE TABLE	1	
12	CYLINDER	SCS 13	1	
11	PISTON	C 3604	1	
10	STEM	SCS 13	1	
9	SEAT	SEE TABLE	1	
8	O-RING	SEE TABLE	1	
7	DISC	FPM	1	
6	DISC HOLDER	SUS 304	1	
5	DISC GUIDE	SCS 13	1	
4	PLUG	SCS 13	1	
3	CAP	FC 200	1	
2	BONNET	SC 480	1	
1	BODY	SC 480	1	

NO	PART NAME	MATERIAL	Q'TY	REMARK
DES	CHE	APP	DATE	2000.11.25
2012.09.21			SCALE	N / S
M.S.LEE	Y.S.KIM	J.K.KIM		
D.W.G NAME			30 kgf/cm2	MODEL NO
PRESSURE REDUCING VALVE				JRV-SF31
 <b>JOKWANG I.L.I CO.,LTD.</b>			D.W.G NO	REV
			JKS-2221001	3

DIMENSION

UNIT : mm

SIZE	d	L	H1	H	FLANGE JIS B 2210 30K RF						W.T (Kg)	Q'TY (EA)
					D	g	C	T	f	N-H		
15A	15	220	67	284	115	55	80	18	1	4-19	15.0	
20A	20	220	67	284	120	60	85	18	1	4-19	15.5	
25A	25	226	67	284	130	70	95	20	1	4-19	16.0	
32A	32	268	85	328	140	80	105	22	2	4-19	25.5	
40A	40	268	85	328	160	90	120	22	2	4-23	25.5	
50A	40	268	85	328	165	105	130	22	2	8-19	25.5	